




**全自动立式插件机 RZS  
Radial inserter RZS**


<b>型号</b>	<b>Model</b>	RZS (一体机)
<b>理论速度</b>	<b>Theoretical speed</b>	0.19 秒/点 0.19sec/pcs
<b>插入方向</b>	<b>Insertion angle</b>	标准: -90°~+90°, 360°可选, 增量为 1° Standard: -90 °~+90 °, 360 ° optional, in increments of 1 °
<b>元件种类</b>	<b>Components style</b>	电容器、晶体管、三极管、LED 灯、按键开关、电阻、连接器、弹簧 、电位器、保险丝座、熔断丝等立式编带封装料,纸带孔距 12.7/15.0mm Vertical tape packaging materials such as capacitors, transistors, LED lights, key switches, resistors, connectors, springs, potentiometers, fuse holders, fuse links, etc., with hole spacing of 12.7mm/15.0mm
<b>元件规格</b>	<b>Components specifications</b>	最大高度为 23mm, 最大直径为 13mm(可定制) Maximum height is 23mm, maximum diameter is 13mm (customizable)
<b>引线跨距</b>	<b>Lead span</b>	双间距 2.5/ 3.5/5.0/7.5/10.0mm(可选配) Double spacing 2.5/ 5.0/7.5/10.0mm (optional)
<b>元件引线剪角长度</b>	<b>Component lead trimming length</b>	1.2~2.2mm(可调) adjustable
<b>元件引线弯角角度</b>	<b>Component lead bending angle</b>	5-45°(可调) adjustable
<b>基板尺寸</b>	<b>Substrate size</b>	50*50mm~400*280mm
<b>基板厚度</b>	<b>Substrate thickness</b>	0.79~2.36mm (标准: 1.6mm) 0.79-2.36mm(Standard: 1.6mm)
<b>线路板输送方式</b>	<b>Circuit board transportation mode</b>	全自动: 左→右 (标准) 或右→左 (选配) Fully automatic: left right (standard) or right left (optional)
<b>基板传送高度</b>	<b>Substrate conveying height</b>	900±20mm
<b>基板传送速度</b>	<b>Substrate transfer speed</b>	3 sec/pcs
<b>PCB 上下元件可通过高度</b>	<b>Components pass through height on PCB</b>	上 23mm/下 8mm 23mm above/8mm below
<b>驱动系统</b>	<b>Driving system</b>	AC 伺服, AC 马达 AC servo, AC motors
<b>孔位校正方式</b>	<b>Hole position offset method</b>	CCD 影像视觉系统, MARK 点视觉校正 CCD image vision system, MARK point visual correction

底座驱动方式	Base drive mode	电磁阀+精密气缸 Imported solenoid valve+precision cylinder
CTA 送料方式	CTA feeding method	电磁阀+精密气缸 Imported solenoid valve+precision cylinder
编程方式	Programming method	离线/在线 (快速扫描编程功能) Offline/Online (Quick scan programming function)
数据输入方式	Data input methods	USB 接口输入(EXCEL 文档格式) USB input (EXCEL document-format)
不良 PCB 板识别	Identification of defective PCB board	具有不良 PCB 板自动识别功能 Automatic recognition function for defective PCB boards
防漏件系统	Leak proof component system	自动识别补料 Automatic identification of replenishment materials
控制系统	Control system	Windows 操作系统中英文界面、视窗平台、液晶显示 Windows operating system, Chinese&English interface, platform, LCD display
MES 系统	MES system	无 Without this feature
使用电源/功率	Power requirement	220V,AC (单相) 50/60HZ , 约 1.5KW Single phase,approximately 1.5kw
使用气压/用气量	Use air pressure/gas	0.6MPA/0.3 立方米/分钟 0.6 mpa/ 0.3 m <sup>3</sup> / min
主机尺寸	Main machine size	L1760mm×W1780mm×H1785mm(10 站) 10 feeders
		L2518mm×W1782mm×H1785mm(20 站) 20 feeders
料站尺寸	Feeder station size	无分体料站 Without split feeder station
机器重量	Machine weight	含 12 站位约 1500KG Approximately 1500kg (with 12 feeders)